

Date of compilation: 17/10/2023 Version: 1

.1	Product identifier:	WCF-XS-C Part A		
	Other means of identification			
	Non-applicable			
L.2	Relevant identified uses of the substance or mixture and uses advised against:			
	Relevant uses: Adhesive for construction			
	Uses advised against: All uses	not specified in this section or in section 7.3		
L.3	Details of the supplier of th	e safety data sheet:		
	"KLIMAS" Sp. z o.o. ul. Wincentego Witosa 135/137 42-233 MYKANÓW - Poland Phone: +48 34 377 71 00 - Fa: office@wkret-met.com www.wkret-met.com			
L.4	Emergency telephone num	ber: +48 112		

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

This product contains less than 1% respirable crystalline silica, so it does not require classification

GB CLP Regulation:

Classification of this product has been carried out in accordance with GB CLP Regulation.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements: GB CLP Regulation:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Supplementary information:

Contains Methacrylic acid, monoester with propane-1,2-diol, Triphenylphosphine.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins



Date of compilation: 17/10/2023 Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
		Methacrylic acid, monoester with propane-1,2-diol	E (10.0)
CAS:	27813-02-1	Eye Irrit. 2: H319; Skin Sens. 1: H317 - Warning	5 - <10 %
		Vinyltoluene	E (10.0)
CAS:	25013-15-4	Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning 🔹 🥠 🏚	5 - <10 %
646	602.25.0	Triphenylphosphine	0.1 .0 5 %
CAS:	603-35-0	Acute Tox. 4: H302; Skin Sens. 1: H317; STOT RE 2: H373 - Warning	0.1 - <0.5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification		Acute toxicity		
Vinyltoluene	LD50 oral	Non-applicable		
CAS: 25013-15-4	LD50 derm	al Non-applicable		
	LC50 inhala	ation 1.5 mg/L (ATEi)		

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.



Date of compilation: 17/10/2023 Version: 1

SECTION 5: FIREFIGHTING MEASURES (continued)

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...). **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

7.2

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



Date of compilation: 17/10/2023 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace: Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

DNEL (Workers):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Methacrylic acid, monoester with propane-1,2-diol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 27813-02-1	Dermal	Non-applicable	Non-applicable	4.2 mg/kg	Non-applicable
EC: 248-666-3	Inhalation	Non-applicable	Non-applicable	14.7 mg/m ³	Non-applicable
Triphenylphosphine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 603-35-0	Dermal	Non-applicable	Non-applicable	0.07 mg/kg	Non-applicable
EC: 210-036-0	Inhalation	Non-applicable	Non-applicable	0.5 mg/m ³	Non-applicable

DNEL (General population):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Methacrylic acid, monoester with propane-1,2-diol	Oral	Non-applicable	Non-applicable	2.5 mg/kg	Non-applicable
CAS: 27813-02-1	Dermal	Non-applicable	Non-applicable	2.5 mg/kg	Non-applicable
EC: 248-666-3	Inhalation	Non-applicable	Non-applicable	8.8 mg/m ³	Non-applicable
Triphenylphosphine	Oral	Non-applicable	Non-applicable	0.01 mg/kg	Non-applicable
CAS: 603-35-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 210-036-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

PNEC:

Identification				
Methacrylic acid, monoester with propane-1,2-diol	STP	10 mg/L	Fresh water	0.904 mg/L
CAS: 27813-02-1	Soil	0.727 mg/kg	Marine water	0.904 mg/L
EC: 248-666-3	Intermittent	0.972 mg/L	Sediment (Fresh water)	6.28 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	6.28 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.3 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



TION 8: EXPOSURE	CUNTRULS/PERSUNAL					
Pictogram	PPE			Remarks		
Mandatory face protection	Panoramic glasses against splas	sh/projections.	Clean daily and disinfect periodicall Use if there	y according to the manufacturer 's instructior e is a risk of splashing.		
E Body protection						
Pictogram	PPE			Remarks		
	Work clothing		to the product for professional, accordance with the regulations in	terioration. For periods of prolonged exposur /industrial users CE III is recommended, in EN ISO 6529:2013, EN ISO 6530:2005, EN IS 2013, EN 464:1994.		
	Anti-slip work shoe	es	to the product for professional,	terioration. For periods of prolonged exposur lindustrial users CE III is recommended, in s in EN ISO 20345:2012 y EN 13832-1:2007		
F Additional emerg	jency measures					
Emergency me	easure Stand	dards	Emergency measure	Standards		
Emergency sh	ISO 3864-1:2011,	Z358-1 , ISO 3864-4:201	.1 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011		
In accordance with t spillage of both the	product and its container. Fo nic Compounds in Paints, 14.15 %	or additional in , Varnishes a % weight	on of the environment it is rec formation see subsection 7.1 Ind Vehicle Refinishing Pro			
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 %	or additional in , Varnishes a % weight plicable	formation see subsection 7.1	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-app AND CHEMICAL PROPE	or additional in , Varnishes a % weight plicable RTIES	oformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap	or additional in , Varnishes a % weight plicable RTIES al properties	oformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-app AND CHEMICAL PROPEI asic physical and chemica	or additional in , Varnishes a % weight plicable RTIES al properties	oformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap AND CHEMICAL PROPEL asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties	oformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance:	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap AND CHEMICAL PROPEL asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties heet.	iformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap AND CHEMICAL PROPEL asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid	iformation see subsection 7.1 Ind Vehicle Refinishing Pro	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 M Appearance: Colour: Odour:	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap AND CHEMICAL PROPEL asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom	iformation see subsection 7.1 Ind Vehicle Refinishing Pro : n atic	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 4 Appearance: Colour: Odour: Odour threshold:	the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-ap AND CHEMICAL PROPEL asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom	nformation see subsection 7.1 Ind Vehicle Refinishing Pro : n	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 Appearance: Colour: Odour: Odour threshold: Volatility:	And CHEMICAL PROPER AND CHEMICAL PROPER Asic physical and chemica ation see the product datash	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a	nformation see subsection 7.1 and Vehicle Refinishing Pro : : n atic applicable *	.D		
In accordance with the spillage of both the spillag	AND CHEMICAL PROPE asic physical and chemica ation see the product datash °C: ospheric pressure:	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a	iformation see subsection 7.1 ind Vehicle Refinishing Pro- m atic applicable * applicable *	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 G Appearance: Colour: Odour: Odour threshold: Volatility: Boiling point at atmos	And the community legislation for product and its container. Fo nic Compounds in Paints, 14.15 % t 20 °C: Non-app Non-app Non-CHEMICAL PROPE Asic physical and chemica ation see the product datash °C: Despheric pressure: 20 °C:	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a	iformation see subsection 7.1 ind Vehicle Refinishing Pro- m atic applicable * applicable *	.D		
In accordance with the spillage of both the spillag	And CHEMICAL PROPER AND CHEMI	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a Non-a	iformation see subsection 7.1 ind Vehicle Refinishing Pro- matic applicable * applicable * applicable * applicable *	.D		
In accordance with the spillage of both the spillag	And CHEMICAL PROPE asic physical and chemical ation see the product datash °C: c: c: c: c: c: c: c: c: c: c	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a Non-a	iformation see subsection 7.1 ind Vehicle Refinishing Pro- m atic applicable * applicable *	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 f Appearance: Odour: Odour: Odour: Odour: Odour: Odour threshold: Volatility: Boiling point at atmode Vapour pressure at 2 Evaporation rate at 2 Product description	And CHEMICAL PROPE asic physical and chemical ation see the product datash °C: c: c: c: c: c: c: c: c: c: c	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a Non-a Non-a	iformation see subsection 7.1 and Vehicle Refinishing Pro- tem atic applicable * applicable * applicable * applicable * applicable * applicable *	.D		
In accordance with the spillage of both the spillag	And CHEMICAL PROPER AND CHEMI	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a Non-a Non-a	iformation see subsection 7.1 ind Vehicle Refinishing Pro- matic applicable * applicable * applicable * applicable *	.D		
In accordance with t spillage of both the The Volatile Organ V.O.C. (Supply): V.O.C. density at TION 9: PHYSICAL Information on ba For complete inform Appearance: Physical state at 20 f Appearance: Odour: Odour: Odour: Odour: Odour: Odour threshold: Volatility: Boiling point at atmode Vapour pressure at 2 Evaporation rate at 2 Product description	And CHEMICAL PROPER asic physical and chemical ation see the product datash °C: 20 °C: 20 °C: 20 °C: 20 °C: 20 °C: 20 °C: 20 °C: 20 °C:	or additional in , Varnishes a % weight plicable RTIES al properties heet. Solid Paste Crear Arom Non-a Non-a Non-a Non-a Non-a Non-a	iformation see subsection 7.1 and Vehicle Refinishing Pro- tem atic applicable * applicable * applicable * applicable * applicable * applicable *	.D		



Date of compilation: 17/10/2023 Version: 1

SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	>20.5 mm²/s
	Concentration:	Non-applicable *
	pH:	7 (at 10 %)
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non-applicable
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	355 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Explosive (Solid):	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable *
9.2	Other information:	
	Information with regard to physical hazard clas	sses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing info	rmation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable



Date of compilation: 17/10/2023 Version: 1

SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - IARC: Vinyltoluene (3); Titanium dioxide (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:
 - Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.



Date of compilation: 17/10/2023 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	Acute toxicity		
Methacrylic acid, monoester with propane-1,2-diol	LD50 oral	11200 mg/kg	Rat	
CAS: 27813-02-1	LD50 dermal	>5000 mg/kg	Rabbit	
	LC50 inhalation	>20 mg/L		
Vinyltoluene	LD50 oral	>5000 mg/kg	Rat	
CAS: 25013-15-4	LD50 dermal	>5000 mg/kg		
	LC50 inhalation	1.5 mg/L (ATEi)		
Triphenylphosphine	LD50 oral	700 mg/kg	Rat	
CAS: 603-35-0	LD50 dermal	>5000 mg/kg		
	LC50 inhalation	>5 mg/L		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Methacrylic acid, monoester with propane-1,2-diol	LC50	833 mg/L (96 h)	Scophthalmus maximus	Fish
CAS: 27813-02-1		210 mg/L (48 h)	Acartia tonsa	Crustacean
	EC50	Non-applicable		
Vinyltoluene	LC50	7.6 mg/L (96 h)	Salmo gairdneri	Fish
CAS: 25013-15-4	EC50	1.3 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	2.6 mg/L (72 h)	Selenastrum capricornutum	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
Methacrylic acid, monoester with propane-1,2-diol	NOEC	Non-applicable		
CAS: 27813-02-1	NOEC	45.2 mg/L	Daphnia magna	Crustacean
Vinyltoluene	NOEC	1.16 mg/L	N/A	Fish
CAS: 25013-15-4	NOEC	0.32 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradab	ility
Methacrylic acid, monoester with propane-1,2-diol	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 27813-02-1	COD	Non-applicable	Period	Non-applicable
	BOD5/COD	Non-applicable	% Biodegradable	81 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
Methacrylic acid, monoester with propane-1,2-diol	BCF	3	
CAS: 27813-02-1	Pow Log	0.97	
	Potential	Low	
Vinyltoluene	BCF	5	
CAS: 25013-15-4	Pow Log	3.44	
	Potential	Low	

12.4 Mobility in soil:



Date of compilation: 17/10/2023 Version: 1

Identification	Absor	ption/desorption		Volatility
Methacrylic acid, monoester with propane-1,2-diol	Кос	80	Henry	9E-4 Pa·m ³ /mo
CAS: 27813-02-1	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Vinyltoluene	Кос	Non-applicable	Henry	Non-applicable
CAS: 25013-15-4	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.2E-2 N/m (20 °C)	Moist soil	Non-applicable
Triphenylphosphine	Кос	Non-applicable	Henry	Non-applicable
CAS: 603-35-0	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	1.168E-2 N/m (408.05 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste:

HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable

- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Non-applicable

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.' Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:



Date of compilation: 17/10/2023 Version: 1

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

Classification procedure:

Skin Sens. 1: Calculation method Aquatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Dose 50 LC50: Effective concentration 50 EC50: Effective concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.



Date of compilation: 17/10/2023 Version: 1

1.1	Product identifier:	WCF-XS-C Part B
	Other means of identification	:
	Non-applicable	
1.2	Relevant identified uses of th	e substance or mixture and uses advised against:
	Relevant uses: Adhesive for cons	truction
	Uses advised against: All uses no	t specified in this section or in section 7.3
1.3	Details of the supplier of the	safety data sheet:
	"KLIMAS" Sp. z o.o. ul. Wincentego Witosa 135/137, l 42-233 MYKANÓW - Poland Phone: +48 34 377 71 00 - Fax: office@wkret-met.com www.wkret-met.com	
1.4	Emergency telephone numbe	r: +48 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation:

Classification of this product has been carried out in accordance with GB CLP Regulation. Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

GB CLP Regulation:

Warning



Hazard statements:

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction.

Precautionary statements:

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

Supplementary information:

Contains Dibenzoyl peroxide .

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, pigments and resins



Date of compilation: 17/10/2023 Version: 1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
		Dibenzoyl peroxide	
CAS:		Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Org. Perox. B: H241; Skin Sens. 1:	10 - <15 %
646		Carbon black	0.1 <0.5.%
CAS:	1333-86-4	Carc. 2: H351 - Warning	0.1 - <0.5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification				M-factor
Dibenzoyl peroxide			Acute	10
CAS: 94-36-0			Chronic	10
	Identification	Speci	ific concentr	ation limit
Dibenzoyl peroxide		% (w/w) >=52: Org. Perox. 35<= % (w/w) <52: Org. Pe	B - H241	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

In case of consumption, seek immediate medical assistance showing the SDS for the product.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:



Date of compilation: 17/10/2023 Version: 1

SECTION 5: FIREFIGHTING MEASURES (continued)

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

6.4

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-inflammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.



Date of compilation: 17/10/2023 Version: 1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
Dibenzoyl peroxide	WEL (8h)		5 mg/m ³
CAS: 94-36-0	WEL (15 min)		
Carbon black	WEL (8h)		3.5 mg/m ³
CAS: 1333-86-4	WEL (15 min)		7 mg/m ³

Nuisance dust: Inhalable dust 10 mg/m3 // Respirable dust 4 mg/m3

DNEL (Workers):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Dibenzoyl peroxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 94-36-0	Dermal	Non-applicable	Non-applicable	13.3 mg/kg	Non-applicable
EC: 202-327-6	Inhalation	Non-applicable	Non-applicable	39 mg/m ³	Non-applicable

DNEL (General population):

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Dibenzoyl peroxide	Oral	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
CAS: 94-36-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 202-327-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

PNEC:

Identification				
Dibenzoyl peroxide	STP	0.35 mg/L	Fresh water	0.00002 mg/L
CAS: 94-36-0	Soil	0.003 mg/kg	Marine water	0.000002 mg/L
EC: 202-327-6	Intermittent	0.000602 mg/L	Sediment (Fresh water)	0.013 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.001 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Date of compilation: 17/10/2023 Version: 1

Odour threshold:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Evaporation rate at 20 °C:

Product description: Density at 20 °C:

Relative density at 20 °C: Dynamic viscosity at 20 °C:

Boiling point at atmospheric pressure:

Volatility:

		CONTRO	OLS/PERSONAL PROTECT	ION (d	continued)		
	Pictogram		PPE		F	Remarks	
7	Mandatory face protection	Panorami	c glasses against splash/projections.	Clean c		according to the manufacturer 's instructions s a risk of splashing.	
E Bod	y protection						
	Pictogram		PPE		F	Remarks	
			Work clothing	to	rioration. For periods of prolonged exposurd dustrial users CE III is recommended, in I ISO 6529:2013, EN ISO 6530:2005, EN IS 13, EN 464:1994.		
			Anti-slip work shoes	to the product for professional/inc		rioration. For periods of prolonged exposu dustrial users CE III is recommended, in n EN ISO 20345:2012 y EN 13832-1:2007	
F Additional emergency measures							
	Emergency measure		Emergency measureStandardsImage: Ansi Z358-1 ISO 3864-1:2011, ISO 3864-4:2011Emergency shower		Emergency measure	Standards	
					Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011	
Enviro	nmental exp	osure co	ontrols:				
spillage The Vo V.O	of both the p	roduct an ic Compo	inity legislation for the protecti d its container. For additional i ounds in Paints, Varnishes 0 % weight 0 kg/m ³ (0 g/L)	nforma	tion see subsection 7.1.D		
CTION 9:	PHYSICAL A	AND CHI	EMICAL PROPERTIES				
			EMICAL PROPERTIES	s:			
Inform	nation on bas	sic physi		s:			
Inform For con Appea	nation on bas nplete informa rance:	sic physi tion see t	cal and chemical properties the product datasheet.				
Inform For con Appea Physica	nation on bas nplete informa rance: I state at 20 º	sic physi tion see t	cal and chemical properties the product datasheet. Solic	1			
Inform For con Appea Physica Appeara	nation on bas nplete informa rance: I state at 20 º ance:	sic physi tion see t	cal and chemical properties the product datasheet. Solic Past	i e			
Inform For con Appea Physica	nation on bas nplete informa rance: I state at 20 º ance:	sic physi tion see t	cal and chemical properties the product datasheet. Solic Past Blac	i e			

1.55

*Not relevant due to the nature of the product, not providing information property of its hazards.

Non-applicable *



Date of compilation: 17/10/2023 Version: 1

SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	>20.5 mm²/s
	Concentration:	Non-applicable *
	pH:	6 (at 10 %)
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Miscible
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non-applicable
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	435 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Explosive (Solid):	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable *
9.2	Other information:	
	Information with regard to physical hazard clas	sses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing info	rmation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:



Date of compilation: 17/10/2023 Version: 1

	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Heating may cause a fire or explosion	Avoid direct impact	Not applicable
.5	Incompatible materials	1			
				Construction of the	Otherus
	Acids	Water	Oxidising materials	Combustible materials	Others

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Produces eye damage after contact.

- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
 - IARC: Glass, oxide, chemicals (1); Carbon black (2B); Dibenzoyl peroxide (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.



Date of compilation: 17/10/2023 Version: 1

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification		Ac	Genus	
Dibenzoyl peroxide		LD50 oral	7710 mg/kg	Rat
CAS: 94-36-0		LD50 dermal	>5000 mg/kg	
		LC50 inhalation	>5 mg/L	
Carbon black		LD50 oral	>5000 mg/kg	
CAS: 1333-86-4		LD50 dermal	>5000 mg/kg	
		LC50 inhalation	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Dibenzoyl peroxide	LC50	0.0602 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 94-36-0	EC50	0.11 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0.071 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Carbon black	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 1333-86-4	EC50	5600 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability		
Dibenzoyl peroxide	BOD5	Non-applicable	Concentration	Non-applicable	
CAS: 94-36-0	COD	Non-applicable	Period	10 days	
	BOD5/COD	Non-applicable	% Biodegradable	68 %	

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

Identification	Absorpt	Absorption/desorption		ility
Dibenzoyl peroxide	Кос	6309.57	Henry	Non-applicable
CAS: 94-36-0	Conclusion	Immobile	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:



Date of compilation: 17/10/2023 Version: 1

SECTION 13: DISPOSAL CONSIDERATIONS (continued)								
	Code	Description	Waste class	I				
	08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous	l				
		•						

Type of waste:

HP14 Ecotoxic, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.


Regulations related to waste management:


In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land: With regard to ADR 2023 and RID 2023:





With regard to IATA/ICAO 2023:



Date of compilation: 17/10/2023 Version: 1

SECTION 14: TRANSPORT INFORMATION (continued)						
	UN number: UN proper shipping name:	UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Dibenzoyl peroxide)				
14.3	Transport hazard class(es):	9				
	Labels:	9				
14.4	Packing group:	III				
14.5	Environmental hazards:	Yes				
14.6	Special precautions for user					
	Physico-Chemical properties:	see section 9				
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable				

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS	100	200

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H410: Very toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation:

Aquatic Acute 1: H400 - Very toxic to aquatic life. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Carc. 2: H351 - Suspected of causing cancer. Eye Irrit. 2: H319 - Causes serious eye irritation. Org. Perox. B: H241 - Heating may cause a fire or explosion. Skin Sens. 1: H317 - May cause an allergic skin reaction.

Classification procedure:



Date of compilation: 17/10/2023 Version: 1

SECTION 16: OTHER INFORMATION (continued)
Eye Irrit. 2: Calculation method
Skin Sens. 1: Calculation method
Aquatic Chronic 1: Calculation method
Advice related to training:
Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.
Principal bibliographical sources:
http://echa.europa.eu
http://eur-lex.europa.eu
Abbreviations and acronyms:
ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.