PRODUCT DATA SHEET - FIP

tel. +48 34 377 71 00, fax. +48 34 328 01 73 Hotline: 801 477 477, www.wkret-met.com



CERTIFIED FOUNDATION HORIZONTAL PERIMETER INSULATION FOIL - FIP

Foundation horizontal perimeter insulation foil FIP is made from low-density polyethylene. Protects building walls against capillary moisture, so prevents moisture from the ground. It is characterized by above-average resistance to tear and wear, which in combination with adequate flexibility, ensures quick and problem-free installation even in corners and any bend types. Resistant to chemicals, fungus, shows no degradation.



Foil conforms with: PN-EN 14909:2012

Section 1. PRODUCT DESCRIPTION

Section 2. TECHNICAL DATA

TECHNICAL PARAMETERS		
Parameter	Unit	Value
Weight	[g/m²]	300 (±30%)
Width	[m]	0,25 / 0,365 / 0,5 (±2%)*
Length	[rm]	50 (±0,4)
Thickness	[mm]	0,3 (±8%)
Roll height	[m]	0,25 / 0,365 / 0,5*
Waterproofness at 2kPa	[-]	fulfilled
Waterproofness after artificial aging	[-]	fulfilled
Waterproofness after exposure to chemicals	[-]	fulfilled
Impact resistance	[mm]	≥ 200
Reaction to fire	class	F
Bending resistance at low temperature	[°C]	-25
Standard	[-]	PN-EN 14909:2012

^{*}for FIP-02550 / FIP-03750 / FIP-05050

Section 3. REMARKS

- All previous versions of this Product Data Sheet shall cease to be valid
- Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.