KLIMAS Sp. z o.o. ul. W. Witosa 135/137 Kuźnica Kiedrzyńska 42-233 Mykanów

tel. +48 34 377 71 00, fax. +48 34 328 01 73 Infolinia: 801 477 477, www.wkret-met.com.pl



PRODUCT DATA SHEET - TM

Section 1. PRODUCT DESCRIPTION

FIXING STRAP - TM

Fixing straps for nailing are made from steel sheet and used mainly for various types of timber-to-timber connections. For connections, the following fasteners can be used: nails, screws, ring shank nails and screws. Angle brackets have their own nailing diagrams. If no information is given it is assumed that they should be fixed using all available holes. Fasteners are coated with blue zinc-plated coating ensuring corrosion protection and come in fire resistance class A1.

Features and advantages of fasteners:

- easy installation
- savings in construction materials
- stability and rigidity of the structure
- high quality, durability and aesthetics
- corrosion protection
- fire resistance class A1






Fasteners conform to European standard: PN-EN 14545:2011

Section 2. METHOD OF INSTALLATION

- Original fasteners delivered by the manufacturer can be used only 1.
- The fastened wooden elements should be defect-free (no knots, cracks, colourations, rots, structure and shape defects, mechanical 2. damages) as any defects reduce their strength
- 3. For connection, suitable pin type fasteners should be selected with an adequate length depending on thickness of the elements to be
- 4. Pin type fasteners should conform to PN-EN 14545:2011
- Screws and nails should be used directly in wooden substrate without prior drilling
- Fasteners should be used in accordance with technical design prepared, taking into account Polish standards and building regulations 6.




KLIMAS Sp. z o.o. ul. W. Witosa 135/137 Kuźnica Kiedrzyńska 42-233 Mykanów

tel. +48 34 377 71 00, fax. +48 34 328 01 73 Infolinia: 801 477 477, www.wkret-met.com.pl



PRODUCT DATA SHEET - TM

Section 3. TECHNICAL DATA



SELECTION TABLE						
Product marking	Dimensions [mm]			No. of holes	Design resistance	Number of pieces in a box
	Α	В	D	ø4,5	[kN]	[rm.]
TM-01010	rm.	40	2	100	1,10	10
TM-02010	rm.	60	2	150	1,10	10
TM-03010	rm.	80	2	200	1,10	10
TM-01025	rm.	40	2	100	1,10	25
TM-02025	rm.	60	2	150	1,10	25
TM-03025	rm.	80	2	200	1,10	25

Section 4. REMARKS

- All previous versions of this Product Data Sheet shall cease to be valid
- Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.