

DECLARATION OF PERFORMANCE No 36/SZ/16

1. Unique identification code of the product-type: **KPR-FAST 12, KPS-FAST 12**
2. Intended use/es: **Plastic anchors for multiple use in concrete and masonry for non-structural applications**
3. Manufacturer: **Klimas Sp. z o.o.
ul. Wincentego Witosa 135/137
Kuźnica Kiedrzyńska 42-233 Mykanów**
4. Authorised representative: **not applicable**
5. System/s of AVCP: **system 2+**
6. European Assessment Document: **ETAG 020/03.2012**
European Technical Assessment: **ETA-12/0272 / 29.06.2018**
Technical Assessment Body: **Instytut Techniki Budowlanej - ITB**
Notified body/ies: **1488**
7. Declared performance/s:

Essential characteristic	Performance									
Utilization category	A	A	B	B	C	C	C	D	D	
anchoring depth heff [mm]	70	70	70	70	70	70	70	70	70	
Base material	Concrete C12/15	Concrete C16/20 - C50/60	Clay bricks MZ	Calcium silicate bricks KS	Vertically perforated clay bricks HLZ	Calcium silicate hollow block KSL	Lightweight concrete hollow blocks HBL	Autoclaved concrete blocks AAC2	Autoclaved concrete blocks AAC7	
Characteristic resistance NRk [kN]	3,50	5,00	3,50	3,50	2,00	3,00	1,50	0,75	3,00	
Displacement δ [mm]	0,55	0,55	0,54	0,56	1,44	0,86	0,12	0,78	0,72	
Min. allowable edge distance cmin [mm]	140	100	100	100	100	100	100	100	100	
Min. allowable spacing smin [mm]	140	100	100	100	100	100	100	100	100	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not applicable**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuźnica Kiedrzyńska
13-09-2018

[place]
[date of issue]

DORADCA TECHNICZNY

mgr inż. Adam Szczepanowski
- 333 -

[name]
[signature]