KLIMAS Sp. z o.o. ul. W. Witosa 135/137 Kuźnica Kiedrzyńska 42-233 Mykanów 48 24 277 71 00 few 48 24 230 01 73 lafoliaio 801 477 477 www.ulrot.mot.com.a

tel. +48 34 377 71 00, fax. +48 34 328 01 73 Infolinia: 801 477 477, www.wkret-met.com.pl



PRODUCT DATA SHEET – TFIB-P

Section 1. PRODUCT DESCRIPTION

ADHESIVE FIBREGLASS TAPE, 30% THINNER - TFIB-P

Adhesive fibreglass tape, 30% thinner TFIB-P is used for reinforcing plasterboard joints, covering small cracks and repairing major cracks in plaster or repairing damages of plasterboard framing. The tape is by 30% thinner compared with the classic tape which makes it ideal for installing plasterboard ceilings.



Section 2. METHOD OF INSTALLATION

- 1. Before application of the tape clean surface of the boards
- 2. Apply adhesive tape on plasterboard joint
- 3. Once plasterboards are joined with tape apply thin layer of joint compound on the tape
- 4. After the compound has dried, apply consequent wider layer until the mesh is immersed completely
- 5. After all layers are applied, smooth out the compound to achieve uniform and smooth surface

Section 3. TECHNICAL DATA

SELECTION TABLE		
Product code	Size (width x length)	Number of pieces in a box
TFIB-04890-P	48 mm x 90 lm	12

Section 4. REMARKS

- 1. All previous versions of this Product Data Sheet shall cease to be valid
- 2. Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.