

PRODUCT DATA SHEET – KSV

Section 1. PRODUCT DESCRIPTION

POLYSTYRENE DISC – KSV



Polystyrene disc KSV is dedicated only to surface mount of ThermoDrive V2 fastener to protect against penetration of wet reinforcing layer inside ThermoDrive V2. It reduces point thermal conductivity of fastener.


Benefits:

- KSV makes easier and faster surface preparing before final ETICS layers works
- KSV reduces point thermal bridges



Section 2. INSTALLATION EXAMPLE

The example of surface mount of ThermoDrive V2 fastener with using KSV polystyrene disc:



Section 3. TECHNICAL DATA

TECHNICAL PARAMETERS		
Parameter	Unit	Value
Diameter	[mm]	13
Thickness	[mm]	20
Point thermal conductivity coefficient	[W/m*K]	≤ 0,038
Bending strength	[kPa]	≥ 150
Dimensions stability	[-]	DS(70,-)2
Reaction to fire	[-]	E
Colour	[-]	biały
Pieces amount in package	[pcs.]	100

Section 4. REMARKS

1. All previous versions of this Product Data Sheet shall cease to be valid
2. Data given in this Product Data Sheet is in accordance with current knowledge and published in good faith. KLIMAS Sp. z o.o. is not responsible for correctness and quality of the fixing if recommendations regarding method of use and installation are not followed.