

DECLARATION OF PERFORMANCE No 30/SZ/16

- Unique identification code of the product-type: **FIXPLUG 8**
- Intended use/es: **Nailed-in plastic anchor for fixing of external thermal insulation composite systems with rendering in concrete and masonry substrates.**
- Manufacturer: **Klimas Sp. z o.o.
ul. Wincentego Witosa 135/137
Kuźnica Kiedrzyńska 42-233 Mykanów**
- Authorised representative: **Not applicable**
- System/s of AVCP: **system 2+**
- European Assessment Document: **a) Guidelines EAD 330196-01-0604 edition 10/2017
b) European Technical Assessment ETA-15/0373 of 07/02/2023
c) Deutsches Institut für Bautechnik – DIBt
d) Technical Assessment Body Nr. 1488**
- Declared performance/s:

Essential characteristic	Performance													
Characteristic resistance	Base material	Concrete C12/15	Concrete C16/20- C50/60	Clay bricks MZ	Calcium silicate bricks KS	Calcium silicate hollow block KSL	Vertically perforated ceramic block MEGA- MAX	Vetically perforated clay brick Porotherm 25	Vertically perforated clay bricks HLZ	Lightweight concrete hollow blocks HBL	Lightweight concrete blocks LAC	Autoclaved concrete blocks 350 kg/m3	Autoclaved concrete blocks 650 kg/m3	
	NRk[kN]	0,60	0,90	0,90	0,90	0,60	NPD	NPD	0,40	0,75	0,60	0,50	0,75	
Edge distances and spacing	Min. allowable spacing smin= 100mm					Min. allowable edge distance cmin= 100mm								
Displacement	N[kN]/ δ[mm]	0,2/0,45	0,3/0,63	0,3/0,73	0,3/0,74	0,2/0,66	NPD	NPD	0,13/0,84	0,25/0,81	0,2/0,80	0,17/0,42	0,25/0,76	
Plate stiffness	Diameter of the anchor plate					60mm								
	Load resistance of the anchor plate					1,4kN								
	Plate stiffness					0,6kN/mm								
Point thermal transmittance	Point thermal transmittance coefficient					0,000W/K								
	Insulation thickness					110-210mm								

NRk – characteristic resistance ; N – tension load ; δ – displacements *) surface mount; **) immersed mount

- Appropriate Technical Documentation and/or Specific Technical Documentation: **Not applicable**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kuźnica Kiedrzyńska
09.02.2023

[place]
[date of issue]

Kierownik działu technicznego

Adam Szczepanowski
- 415 -
[name]

[signature]